

# COILS FOR SOLENOID VALVE BODIES



## TECHNICAL FEATURES

- > All coils are produced with copper wire in H class (180° C)
- > 30% glass fibre thermoplastic body, insulation class F (155 suitable for continuous duty ( 100 % ED )
- > IP65 protection degree.
- > Voltage tolerance : +10% in ac and +10-5 % in dc
- > Electrical connector over 2P+ DIN 43650 socket

## NOTE

- > When used at 60 Hz, the pressure values indicated in the valve body tables should be reduced by approx 12%
- > With DC voltage coils, the pressure values indicated in the valve body tables should be reduced by approx 60%

## HOMOLOGATION AND STANDARDS

- > Complies with EN 60335-1 standards
- > CE: CI02410

## COILS SUITABLE FOR SOLENOID VALVES TYPES 20, 23 AND 63

TYPE	Power Supply	Starting Power VA	Active Power W	Max Working Temp °C
C12DC	12 Vdc	-	12	80
C24DC	24 Vdc	-	12	80
C24AC	24 Vac	25	9	80
C110	110 Vac	25	9	80
C230	230 Vac	25	9	80

## COILS SUITABLE FOR SOLENOID VALVES TYPES 21, 22 AND 29

TYPE	Power Supply	Starting Power VA	Active Power W	Max Working Temp °C
C24-B	24 Vac	33	14	80
C230-B	2230 Vac	33	14	80

# CONNECTOR FOR C RANGE COILS

## TECHNICAL FEATURES

- > Push on connector in compliance with DIN 43650, suitable for all coils
- > Cable gland (cable dia. 6 to 8 mm)

TYPE	Description
1578501	Rotational connector DIN 43650

